


TYPICAL PLAYGROUND EDGING TO SOFTFALL RUBBER  
SCALE 1:5

**NOTES:**

1. ALL DIMENSIONS IN MILLIMETERS UNLESS NOTED OTHERWISE.
2. CONCRETE STRENGTH: N32/10.
3. ALL PLAYGROUND CONCRETE EDGING IS TO BE REINFORCED. REINFORCING BARS TO AS1302. CRACK CONTROL EVERY 3m.
4. NO EXTRUDED CONCRETE - ('KWIK KERB') EDGING WITH OR WITHOUT FIBER REINFORCING IS TO BE USED.
5. PLAYGROUND EDGING IS TO BE FLUSH WITH ABUTTING GROUND SURFACES, UNLESS NOTED OTHERWISE.
6. ALL PLAYGROUND SOFTFALL MATERIAL TO BE CERTIFIED FOR COMPLIANCE WITH AS/NZ-4422.
7. SOFTFALL RUBBER TILES TO BE IN ACCORDANCE WITH MRC SUPPLEMENTARY SPECIFICATION 8511.
8. SOFTFALL RUBBER TILES TO BE 16mm THICK AND FOR EXTERNAL USE ONLY. NO INDOOR PRODUCTS ARE PERMITTED
9. SURFACE THICKNESS OF UNITARY SOFTFALL (TRAFFICABLE SOFTFALL) TO EXCEED EQUIPMENT'S SPECIFIED CRITICAL FALL HEIGHT REQUIREMENT BY 30% TO ALLOW FOR COMPACTION OF SURFACE OVER DURATION OF ASSETS LIFE
10. 2.3 GRANULAR IS TO BE COMPACTED IN LAYERS NOT EXCEEDING 100mm IN DEPTH USING A VIBRATING PLATE.
11. RUBBER TILE AND SHOCK PAD JOINTS TO BE STAGGERED.
12. ADHESIVE UNDER THE TILES MUST HAVE 100% COVERAGE AND TILES MUST BE ROLLED WITH 50kg + FLOORING ROLLER AFTER INSTALLATION. REFER MANUFACTUROR'S INSTALLATION MANUAL

FILE NAME \STANDARD DRAWINGS\A4-00584



F	01/06/23	AMENDED NOTATION 9 & 10	
NO.	DATE	DESCRIPTION	APPVD
AMENDMENTS AND REVISIONS			

DRAWN	SIGNED	DATE	DIRECTOR ENGINEERING AND COMMERCIAL INFRASTRUCTURE
G Tr	G. TREDOUX	22.02.17	
DESIGNED	SIGNED	DATE	
R W	Ross Willis	10/05/17	
CHECKED	SIGNED	DATE	ORIGINAL SIGNED BY
R W	Ross Willis	10/05/17	GERARD CARLYON
MANAGER PARKS			DATE
ORIGINAL SIGNED BY		30/05/17	30/5/17
P. OWEN	DATE		

**Mackay**  
REGIONAL COUNCIL

WORKS JOB No.	DRAWING No.	AMEND.
STANDARD	A4-00584	F
<b>STANDARD</b>		
<b>TYPICAL PLAYGROUND EDGING TO SOFTFALL RUBBER</b>		