


NOTE:  
THE HANDLE OF THE VALVE MUST MAINTAIN A MINIMUM 50mm CLEARANCE FROM VALVE BOX, GRAVEL LAYER AND OTHER IRRIGATION COMPONENTS IN ALL POSITIONS FROM FULLY SHUT TO FULLY OPEN

TYPICAL ISOLATION VALVE INSTALLATION  
(FOR MANUAL MAINLINE ISOLATION)

DRAWING NOT TO SCALE

		SURVEY		DRAWN DJA	SIGNED A. PICKERING	DATE 17/03/15	DIRECTOR DEVELOPMENT SERVICES		SHEET 1 OF 1	
		SURVEY FILE No		DESIGNED AP	SIGNED A. PICKERING	DATE 16/04/15			WORKS JOB No. -	
A	ORIGINAL ISSUE	LEVEL DATUM		CHECKED -	SIGNED -	DATE -			DRAWING No. A3-08419	
DATE	DESCRIPTION	APPVD	MERIDIAN	MANAGER PARKS & ENVIRONMENT		ORIGINAL SIGNED BY PETER OWEN	DATE 20.5.15	DATE 21/5/15	STANDARD IRRIGATION ISOLATION VALVE FOR MANUAL MAINLINE ISOLATION	
AMENDMENTS AND REVISIONS										
\\STANDARD DRAWINGS\A3-08419										