



OPTION A

OPTION B

**MEDIAN PLANTING
SUBSOIL DRAINAGE DETAIL**
NOT TO SCALE

NOTES:

1. ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE.
2. 300mm WIDE STRIP MUST BE INSTALLED TO ALL STATE CONTROLLED ROADS. THE STRIP IS OPTIONAL OR AS NOMINATED ON PROJECT DRAWINGS FOR LOCAL ROADS.
3. ALL SUBSOIL DRAINAGE IS TO BE CONNECTED TO NEAREST STORMWATER SYSTEM.
4. ALLOW FOR 1 SUBSOIL DRAINAGE CLEANOUT POINT PER DRAINAGE LINE. REFER MRC STANDARD DRAWING A3-0867 FOR SUBSOIL DRAIN CLEANOUT DETAILS.
5. IMPORTED TOPSOIL SHALL BE TO AS4419 STANDARDS. WHERE EXISTING SITE-WORN SOIL IS USED, SOIL IS TO BE AMELIORATED TO COMPLY WITH AS 4418. SOIL TESTS ARE TO BE SUBMITTED TO LANDSCAPE SUPERINTENDANT AND MRC REPRESENTATIVE PRIOR TO DELIVERING ON SITE. THIS FORMS A HOLD POINT.
6. ONLY ORGANIC MULCH TO BE USED, MULCH SHALL BE AS4454. INORGANIC MULCH SUCH AS PEBBLES OR ROCK BELOW Ø30 mm ARE NOT PERMITTED. MULCH TESTS ARE TO BE SUBMITTED TO LANDSCAPE SUPERINTENDANT AND MRC REPRESENTATIVE PRIOR TO DELIVERING ON SITE. THIS FORMS A HOLD POINT.

FILE NAME \STANDARD DRAWINGS\IPARKS\A4-00176.DWG

D	14/1/21	NOTES REVISED	Jason Cocker
NO.	DATE	DESCRIPTION	APPVD
AMENDMENTS AND REVISIONS			

DRAWN	SIGNED	DATE	DIRECTOR
I BENTLEY		12/12/06	ENGINEERING AND
DESIGNED	SIGNED	DATE	COMMERCIAL INFRASTRUCTURE
CHECKED	SIGNED	DATE	ORIGINAL SIGNED BY S.HOLLEY
G HAWES		12/12/06	JASON DEVITT
MANAGER TECHNICAL SERVICES			DATE 12/12/06
G.HAWES		28.11.13	
G. HAWES RPEQ 5693		DATE	

Mackay
REGIONAL COUNCIL

WORKS JOB No.	DRAWING No.	AMEND.
	A4-00176	D
STANDARD MEDIAN PLANTING SUBSOIL DRAINAGE		