


NOTE:
 THE HANDLES OF VALVES MUST MAINTAIN A MINIMUM
 50mm CLEARANCE FROM VALVE BOX, GRAVEL LAYER
 AND OTHER IRRIGATION COMPONENTS IN ALL
 POSITIONS FROM FULLY SHUT TO FULLY OPEN

TYPICAL SOLENOID VALVE INSTALLATION
 FOR SPRINKLERS WITH MAINLINE FILTER

DRAWING NOT TO SCALE

		SURVEY		DRAWN DJA	SIGNED A. PICKERING	DATE 17/03/15	DIRECTOR DEVELOPMENT SERVICES		SHEET 1 OF 1	
		SURVEY FILE No		DESIGNED AP	SIGNED A. PICKERING	DATE 16/04/15			WORKS JOB No. -	
A	ORIGINAL ISSUE	LEVEL DATUM		CHECKED -	SIGNED -	DATE -			DRAWING No. A3-08423	
DATE	DESCRIPTION	APPVD	MANAGER PARKS & ENVIRONMENT		ORIGINAL SIGNED BY PETER OWEN		DATE 20.5.15	STANDARD IRRIGATION SOLENOID VALVE FOR SPRINKLERS WITH FILTER MAINLINE		
AMENDMENTS AND REVISIONS			MERIDIAN		ORIGINAL SIGNED BY PETER OWEN		DATE 21/5/15			
\STANDARD DRAWINGS\A3-08423										