



- NOTE:
1. TOP OF VALVE BOX LIDS TO BE FLUSH WITH FINISHED GRADE IN LAWN AREAS. LID TO BE 50mm PROUD IN GARDEN AREAS.
  2. ALL IRRIGATION COMPONENTS TO HAVE SWIVEL UNIONS ON EITHER SIDE.
  3. MIN. 50mm CLEARANCE BETWEEN IRRIGATIONS COMPONENTS AND VALVE BOX IN ALL DIRECTIONS.

**TYPICAL MAIN FILTER INSTALLATION**  
UNDERGROUND (25mm AND SMALLER)

DRAWING NOT TO SCALE

		SURVEY		DRAWN DJA	SIGNED A. PICKERING	DATE 17/03/15	DIRECTOR DEVELOPMENT SERVICES		SHEET 1 OF 1	
		SURVEY FILE No		DESIGNED AP	SIGNED A. PICKERING	DATE 16/04/15	ORIGINAL SIGNED BY GERARD CARLYON		WORKS JOB No.	
A		LEVEL DATUM		CHECKED -	SIGNED -	DATE -			DRAWING No.	
DATE		DESCRIPTION		MANAGER PARKS & ENVIRONMENT		DATE		A3-08416		A
APPVD		MERIDIAN		ORIGINAL SIGNED BY PETER OWEN		DATE 20.5.15		Mackay REGIONAL COUNCIL		STANDARD IRRIGATION MAIN FILTER - UNDERGROUND
AMENDMENTS AND REVISIONS										
\\STANDARD DRAWINGS\IRRIGATION\A3-08416										