


- NOTE:
1. FLUSH VALVES TO BE INSTALLED AT FURTHEREST POINT FROM SOURCE. ONE VALVE TO BE USED FOR EVERY 30 L/MIN OF FLOW
 2. MIN. 50mm CLEARANCE BETWEEN IRRIGATION COMPONENTS AND VALVE BOX IN ALL DIRECTIONS

TYPICAL DRIP FLUSH VALVE INSTALLATION

DRAWING NOT TO SCALE

		SURVEY		DRAWN DJA	SIGNED A. PICKERING	DATE 17/03/15	DIRECTOR DEVELOPMENT SERVICES		SHEET 1 OF 1		
		SURVEY FILE No		DESIGNED AP	SIGNED A. PICKERING	DATE 16/04/15	ORIGINAL SIGNED BY GERARD CARLYON		WORKS JOB No. -		
A	ORIGINAL ISSUE	LEVEL DATUM		CHECKED -	SIGNED -	DATE -			DRAWING No. A3-08434		AMEND. A
DATE	DESCRIPTION	APPVD	MERIDIAN	MANAGER PARKS & ENVIRONMENT			DATE	21/5/15	 <p>STANDARD IRRIGATION DRIP FLUSH VALVE</p>		
AMENDMENTS AND REVISIONS			ORIGINAL SIGNED BY PETER OWEN	DATE	20.5.15						
\\STANDARD DRAWINGS\A3-08434											