

## Asphaltic Pavement Thickness

**Issue Date** August 2022

**Department** Development Services

**Program** Development Planning and Engineering

**NUMBER**

# DPE01

### 1 Purpose of this Information Bulletin

To provide clear and concise instructions relating to asphaltic pavement thickness where using AC10M.

### 2 Details

Council's Standard Drawings A3-3618 Local Street Cross Section Access Place Urban and A3-3617 Local Street Cross Section Access Street Urban prescribes a minimum 30mm of asphalt pavement where using AC10M.

Planning Scheme Policy – Pavement Design v1.1 took effect on 1 March 2021. As part of this amendment, s5.4 Asphaltic concrete prescribes that for asphalt pavement thickness up to 35mm, AC10M must be used. This applies to the construction of Access Place and Access Street roads.

Interpretation of Council's Standard Drawings and Planning Scheme Policy – Pavement Design v1.1, has been raised with a request sought for clarification on Council's position as to whether the minimum asphalt pavement thickness is 30mm or 35mm where using AC10M.

### 3 Position Statement

Where using AC10M, a minimum asphalt pavement thickness of 30mm is acceptable. This applies to the construction of Access Place and Access Streets across the Mackay Region.

### 4 Date of Effect

5 August 2022.

### 5 Enquiries

Please direct enquiries concerning this Information Bulletin to Council's Development Planning and Engineering Program by telephoning 1300 MACKAY (1300 622 529) or emailing [development.services@mackay.qld.gov.au](mailto:development.services@mackay.qld.gov.au).