



MINOR COLLECTOR STREET
 (TYPICALLY <250 VPD) (FULL WIDTH SEAL)
 8.0m FORMATION
 8.0m SEAL
 SCALE 1 : 100

ACCEPTABLE DESIGN SOLUTIONS (REFERENCE "QUEENSLAND STREETS ")

TRAFFIC
 TYPICALLY <250VPD

DESIGN SPEED
 MAXIMUM DESIGN SPEED 60 km/h

LONGITUDINAL GRADE
 MAXIMUM GRADE 16%. MINIMUM GRADE 0.2%

SURFACING
 16 & 10 mm TWO COAT BITUMEN SEAL

RESIDENTIAL ACCESS FUNCTION
 INDIVIDUAL

STREET LIGHTING
 IN ACCORDANCE WITH AUSTRALIAN STANDARD 1158.

INTERSECTIONS
 ONE HUNDRED (100) METRE INTERSECTION SPACINGS.

DRAINAGE.
 MINOR STORM - 1 IN 5 YEAR RETURN PERIOD. CROSS DRAINAGE Q5, Q100 TRAFFICABLE.
 MAJOR STORM - 1 IN 100 YEAR RETURN PERIOD. FLOWS IN EXCESS OF THE MAJOR STORM
 TO HAVE A POSITIVE RELIEF OUTLET. LONGITUDINAL FLOWS ARE TO BE CONTAINED WITHIN
 THE TABLE DRAIN.

GUIDEPOSTS
 GUIDEPOST MATERIALS & ERECTION SPECIFIED IN C263. SPACING AS OUTINED IN MUCTD.

STANDARD DRAWINGS
 PA3 - 865 STANDARD KERBS AND CHANNELS
 PA3 - 867 STANDARD SLOTTED P.V.C. PIPE SUB-SOIL DRAIN
 A2 - 500 STANDARD CONCRETE FOOTPATH
 A4 - 25 TYPICAL MINOR ACCESS DEATAILS RURAL ROADS

RURAL 7

DRAWING FILE NAME

\\MISC\ROAD HIERACHYA3-3601.DWG

NO.	DATE	DESCRIPTION	APPVD.
B	30/01/08	REFERENCE REVISED	GH
A	12/10/06	UNSEALED SHOULDERS DELETED	G.HAWES
AMENDMENTS AND REVISIONS			

DESIGNED
 DRAWN
 CHECKED
 DATE 26/07/06
 M.A.S. ORIGINAL SIGNED
 BY G. HAWES
 12/09/06 G. HAWES
 RPEQ 5693



EXECUTIVE MANAGER
 INFRASTRUCTURE SERVICES
 ORIGINAL SIGNED BY S.M. HOLLEY
 STUART HOLLEY
 DATE 13/09/06
 PHONE (07) 4968 4477
 FAX (07) 4944 2431

COLLECTOR STREET
CROSS SECTION
 MINOR COLLECTOR - SEALED
 (RURAL)

DRAWING No.
A3-3605
 AMEND. **B**
 SHEET 1 OF 1