



PREMIUM STOP

SCALE 1:50

GENERAL LAYOUT

- ALL BUS STOPS TO BE DISABILITY STANDARDS ACCESSIBLE PUBLIC TRANSPORT (DSAPT) COMPLIANT.
- EACH SITE IS UNIQUE WITH DIFFERENT REQUIREMENTS TO BE TAKEN INTO ACCOUNT. REFER CHAPTER 5 - BUS STOP INFRASTRUCTURE, PUBLIC TRANSPORT INFRASTRUCTURE MANUAL, DEPARTMENT OF TRANSPORT AND MAIN ROADS.
- HARDSTAND DESIGN ALLOWS FOR FUTURE RETRO-FIT OF SHELTERS (6922mm X 1595mm) AND OTHER FURNITURE.
- CURRENT AND FUTURE CIRCULATION OF WHEELCHAIRS SHOULD BE CONSIDERED AT EACH BUS STOP BASED ON SITE CONDITIONS. SITE SPECIFIC KERB ACCESS RAMP AND CONNECTOR PATH TO BE DESIGNED AS REQUIRED. SEE TYPE A KERB RAMP ON MRC STD DRAWING A2-00576 AND CONCRETE FOOTPATH ON MRC STD DRAWING A2-00500 FOR DETAILS.
- ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE.

HARDSTAND AREA

- HARDSTAND AREA SHALL BE FULL VERGE WIDTH (KERB TO PROPERTY BOUNDARY), MINIMUM 215mm THICK BROOM FINISHED (FOR SLIP RESISTANCE) GRADE N32 CONCRETE SL72 REINFORCING MESH PLACED CENTRALLY OR AN EQUIVALENT FIBRE REINFORCED CONCRETE SLAB. BOARDING POINT MUST BE AT LEAST 150mm HIGHER THAN THE ROAD SURFACE.
- THE MANDATORY MINIMUM BOARDING POINT IS SHOWN HATCHED ON THIS DRAWING. THIS AREA (2070mm x 2070mm) IS TO REMAIN CLEAR OF ALL FURNITURE EXCEPT TGSIS, UNLESS APPROVAL FROM MTDIP IS SOUGHT TO REDUCE TO 1540mm x 2070mm DUE TO SITE CONSTRAINTS.
- THE CROSSFALL GRADIENT AT BOARDING POINT IS MAXIMUM 1:40. ALL OTHER HARDSTAND AREAS TO ACHIEVE A GRADIENT OF 1:20 TO COMPLY WITH DISABILITY STANDARDS.

FURNITURE

- A CLEAR HARDSTAND ACCESS SPACE OF 1500mm IS REQUIRED BETWEEN AND AROUND ALL BUS STOP INFRASTRUCTURE, UNLESS APPROVAL FROM MTDIP IS SOUGHT TO REDUCE TO 1200mm DUE TO SITE CONSTRAINTS.
- TACTILE GROUND SURFACE INDICATORS (TGSIS) SHALL BE INSTALLED PERPENDICULAR TO THE KERB AND ACROSS THE FULL WIDTH OF THE PATH OF TRAVEL, TO EXTEND TO THE SHORELINE. ALL FURNITURE SHOULD BE A MINIMUM 300mm CLEAR OF TGSIS. TGSIS TO COMPLY WITH AS1428 AND IN ACCORDANCE WITH MRC SUPPLEMENTARY SPECIFICATION 8500.
- BUS STOP IDENTIFICATION MARKER TO BE J-POLE STYLE. REFER TO MRC STD DWG A3-00863 FOR DETAILS. BUS ZONE SIGNS R5-20(R) AND R5-20(L) TO BE INSTALLED AT THE BUS ZONE EXTENTS. BUS ZONE TO BE MARKED BY BROKEN YELLOW ZONE LINE 80MM TO 100mm WIDE WITH 600mm LINE SEGMENTS AND 900mm GAPS PLACED PARALLEL TO THE KERB.
- SEAT TO BE PARKWAY TYPE AND SUPPLIED BY GOSSI PARK & STREET FURNITURE. THE SEAT REQUIRES "CLASSIC COAST ARMS" AND FLANGE MOUNT LEGS. SEAT TO BE CLEAR ANODISED PLANKS ON BLUE "DEEP OCEAN" POWDER COATED LEGS. REFER TO MANUFACTURES INSTRUCTIONS.
- STREET LIGHTING TO BE UTILIZED WHERE POSSIBLE (MINIMUM 2.5m ON DEPARTURE SIDE OF THE BUS IDENTIFICATION MARKER). CRIME PREVENTION THROUGH ENVIRONMENTAL DESIGN (CPTED) PRINCIPLES TO BE APPLIED. ADDITIONAL BUS STOP LIGHTING TO BE PROVIDED ONLY WITH MACKAY REGIONAL COUNCIL APPROVAL.
- SHELTER TO BE PARKLAND TYPE AND SUPPLIED BY GOSSI PARK & STREET FURNITURE. THE SHELTER ROOF TO BE "SURFMIST" AND THE FRAME AND PANELS TO BE "BLUE NIGHT". SHELTER TO COMPLY AND IN ACCORDANCE WITH MRC SUPPLEMENTARY SPECIFICATION 8503. REFER TO MANUFACTURER INSTRUCTIONS AND DIRECTION FROM MTDIP FOR SHELTER SIZE AND CONFIGURATION.

VEGETATION

- VEGETATION MUST NOT OBSTRUCT SIGHT LINES BETWEEN APPROACHING BUS AND PASSENGERS, SHELTERS OR SEATS. VEGETATION MUST NOT OBSTRUCT PASSIVE SURVEILLANCE AT STOP (CPTED). TREE TRUNKS MUST BE CLEAR OF VEGETATION FOR A MINIMUM OF 4.5m FROM UNDERSIDE OF TREE CANOPY. TREES ARE TO BE SET BACK A MINIMUM 600mm FROM FACE OF KERB.

C:\Users\benjamin\OneDrive - MRC\Ben\Drawings\Bus Stop\Bus Stop - premium-Final.dwg

NO.	DATE	DESCRIPTION	APPVD	SURVEYED BY	DRAWN	SIGNED	DATE	ASSET OWNER
C	20/07/22	REVISED DESIGN						
B	7/12/18	DISABLED PAVEMENT MARKING NOT REQ'D	GH					
A		UPDATED STANDARDS						
AMENDMENTS AND REVISIONS								
				SURVEY FILE No	DESIGNED	SIGNED	DATE	SIGNED BY RPEQ 6430
				LEVEL DATUM	CHECKED	SIGNED	DATE	CERTIFIED
				A.H.D.	MANAGER / CO-ORDINATOR			
				HOR. DATUM / DATE	ORIGINAL SIGNED BY C. BROWN		12/8/10	JASON DEVITT
				MGA 94/2020	G. HAWES RPEQ 5693		DATE	12/8/10



**STANDARD
BUS STOP STANDARDS
PREMIUM STOP (URBAN)**

SHEET 1 OF 1	
WORKS JOB No.	
DRAWING No.	AMEND.
A3-00873	C