


**MEDIAN PLANTING  
SUBSOIL DRAINAGE DETAIL**  
NOT TO SCALE


**NOTES:**

1. ALL DIMENSIONS IN MILLIMETRES UNLESS NOTED OTHERWISE.
2. 300mm WIDE STRIP MUST BE INSTALLED TO ALL STATE CONTROLLED ROADS. THE STRIP IS OPTIONAL OR AS NOMINATED ON PROJECT DRAWINGS FOR LOCAL ROADS.
3. ALL SUBSOIL DRAINAGE IS TO BE CONNECTED TO THE NEAREST STORMWATER SYSTEM.
4. ALLOW FOR ONE SUBSOIL DRAINAGE CLEANOUT POINT PER DRAINAGE LINE. REFER MRC STANDARD DRAWING A3-00867 FOR SUBSOIL DRAIN CLEANOUT DETAILS.
5. IMPORTED TOPSOIL SHALL BE TO AS4419 STANDARDS. WHERE EXISTING SITE-WORN SOIL IS USED, SOIL IS TO BE AMELIORATED TO COMPLY WITH AS 4418. SOIL TESTS ARE TO BE SUBMITTED TO LANDSCAPE SUPERINTENDANT AND MRC REPRESENTATIVE PRIOR TO DELIVERING ON SITE. THIS FORMS A HOLD POINT.
6. ONLY ORGANIC MULCH TO BE USED. MULCH SHALL BE AS4454. INORGANIC MULCH SUCH AS PEBBLES OR ROCK BELOW Ø30 mm ARE NOT PERMITTED. MULCH TESTS ARE TO BE SUBMITTED TO LANDSCAPE SUPERINTENDANT AND MRC REPRESENTATIVE PRIOR TO DELIVERING ON SITE. THIS FORMS A HOLD POINT.
7. THIS STANDARD DRAWING SHALL BE READ IN CONJUNCTION WITH MRC SUPP SPEC 8107 - SUBSOIL DRAINAGE.

FILE NAME I STANDARD DRAWINGS\ PARKS\ A4-00176.DWG

E	15/04/26	MINOR AMENDMENTS	 APPVD
NO.	DATE	DESCRIPTION	
AMENDMENTS AND REVISIONS			

DRAWN	SIGNED	DATE	DIRECTOR ENGINEERING AND COMMERCIAL INFRASTRUCTURE
I BENTLEY		12/12/06	
DESIGNED	SIGNED	DATE	ORIGINAL SIGNED BY S.HOLLEY JASON DEVITT
G HAWES		12/12/06	
CHECKED G HAWES MANAGER TECHNICAL SERVICES			DATE 28.11.13
G.HAWES RPEQ 5693			DATE 28.11.13



**Mackay**  
REGIONAL COUNCIL

WORKS JOB No.	DRAWING No.	AMEND.
	A4-00176	E
<b>STANDARD MEDIAN PLANTING SUBSOIL DRAINAGE</b>		